



ACCESSORIES KIT

Product Benefits

- Long life, thanks to the use of high-quality materials
- Endurance to high temperatures
- Stainless steel hose with insulation and UV protection
- Brass fittings
- Easy and quick installation

5
YEAR
WARRANTY
for the
SOLAR
TANK



ACCESSORIES KIT



Technical data

Connection fittings	brass, mechanical compression or threaded with permatite sealant
Connection hose	inox 316L, spiral with UV-protected insulation
Expansion vessel capacity [lt]	standard included, 0,5 or 1 or 1,5 or 2
Close loop circuit safety valve	standard included, brass, pre-set to 2bar
DHW Safety valve	standard included, brass, pre-set to 8bar
Header internal reinforcement (stern)	standard included, brass
Header closure caps	standard included, brass, mechanical compression
Heat transfer medium	standard included, polypropylene glycol
MAX Operating pressure [bar]	10
Labeling	according to customer specification to material, nr, position and language
Packaging	carton box or bulk
Palletizing	according to customer specification



92.000 Total m² of plant area
528.000 Average m² of absorbent surface produced annually
44 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece
 tel: +30 27510 20920-2
www.dimas-solar.gr | sales@dimas-solar.gr