



FIN PLUS U-TYPE



- High durability and long-life operation thanks to the use of high-quality materials
- Highly absorbent surface, with blue or black selective PVD coating
- Aluminum sheet and copper tube welded with LASER Technology
- Contemporary method for zero loss test
- Production flexibility offering a wide range of sizes up to 9 m², in any combination.
- Original equipment manufacturer (OEM)





www.dimas-solar.gr



FIN PLUS absorbers & strips series

FIN PLUS U-TYPE

Technical data

L x W x H [mm]	according to customer specification
Curve angle	according to customer specification
Absorber sheet	pvd, blue, selective aluminium or specific paint, black, aluminium
Ø Riser [mm]	8 or 10 or 12 or 15
Absorptive sheet welding method	laser
Proper heat tranfer medium	polypropylene glycol and water mixture
MAX Operating pressure [bar]	10
Labeling	according to customer specification to material, nr, position and language
Packaging	according to customer specification
Labeling	according to customer specification to material, nr, position and language
Packaging	according to customer specification
Palletizing	according to customer specification



92.000 Total m² of plant area
528.000 Average m² of absorbent surface produced annually
44 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece tel: +30 27510 20920-2 www.dimas-solar.gr | sales@dimas-solar.gr