



GRILL PLUS absorbers & strips series

GRILL PLUS CUST

Product Benefits

- High durability and long-life operation thanks to the use of high-quality materials
- Highly absorbent surface, with blue or black selective PVD coating
- Aluminum sheet and copper tube welded with LASER Technology
- Contemporary method for zero loss test
- Production flexibility offering a wide range of sizes up to 9 m², in any combination.
- Original equipment manufacturer (OEM)





www.dimas-solar.gr



GRILL PLUS absorbers & strips series

GRILL PLUS CUST

Technical data

L x W x H [mm]	according to customer specification
Orientation	vertical or horizontal
Ø Header [mm]	18 or 22 or 28
Ø Riser [mm]	8 or 10 or 12 or 15
NR of header outlets	4or3or2
Outlets type	plain tube or brass fittings
Header to riser connection method	brazing, copper-based wire
Proper heat tranfer medium	polypropylene glycol and water mixture
MAX Operating pressure [bar]	10
Labeling	according to customer specification to material, nr, position and language
Packaging	according to customer specification
Palletizing	according to customer specification



92.000 Total m² of plant area
528.000 Average m² of absorbent surface produced annually
44 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece tel: +30 27510 20920-2 www.dimas-solar.gr | sales@dimas-solar.gr