



# NEO PLUS

## mounting structures

### NEO PLUS COL

### Product Benefits

- Durability and long-life operation, thanks to the use of high-quality materials
- Stability in extreme weather conditions (physical controls)
- Easy transport
- Quick installation
- Flexibility and production precision, thanks to contemporary machinery

**10**  
**YEAR**  
WARRANTY



**NEO PLUS**  
mounting structures



**NEO PLUS COL**

**Technical data**

Approved collector models	all sizes(1,5 to 2,9 m <sup>2</sup> ) with vertical or horizontal position
Approved nr of installed collector	1 or 2
Approved tank models	n/a
Inclination range [°]	15-75
Structure material	steel
Structure surface treatment	hot-dip galvanization or aluzinc or magnelis process
Structure thickness [mm]	1,5 or 2
Collector support type	C-shape or T-shape
Connection material	galvanized or inox 304 steel
Connection to ground	standard included solution or according to customer specification
Labeling	according to customer specification to material, nr, position and language
Packaging	carton box or bulk or according to customer specification
Palletizing	according to customer specification



**92.000** Total m<sup>2</sup> of plant area  
**528.000** Average m<sup>2</sup> of absorbent surface produced annually  
**44 years** of experience

2nd km Argos-Nafplio | 21200, Argos, Greece  
 tel: +30 27510 20920-2  
[www.dimas-solar.gr](http://www.dimas-solar.gr) | [sales@dimas-solar.gr](mailto:sales@dimas-solar.gr)