



NEO PLUS

mounting structures

NEO PLUS FLAT

10
YEAR
WARRANTY

Product Benefits

- Durability and long-life operation, thanks to the use of high-quality materials
- Stability in extreme weather conditions (physical controls)
- Easy transport
- Quick installation
- Flexibility and production precision, thanks to contemporary machinery



NEO PLUS
mounting structures



NEO PLUS FLAT

Technical data

Approved collector models	all sizes(1,5 to 2,9 m ²) with vertical or horizontal position
Approved nr of installed collector	1 or 2
Approved tank models	all sizes(120 to 500 lt)
Inclination range [°]	15-75
Structure material	steel
Structure surface treatment	hot-dip galvanization or aluzinc or magnelis process
Structure thickness [mm]	1,5 or 2
Collector support type	C-shape or T-shape
Connection material	galvanized or inox 304 steel
Connection to ground	standard included solution or according to customer specification
Labeling	according to customer specification to material, nr, position and language
Packaging	carton box or bulk or according to customer specification
Palletizing	according to customer specification



92.000 Total m² of plant area
528.000 Average m² of absorbent surface produced annually
44 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece
 tel: +30 27510 20920-2

www.dimas-solar.gr | sales@dimas-solar.gr