



# NEO PLUS

## mounting structures

### NEO PLUS UNIVERSAL

**10**  
**YEAR**  
WARRANTY

### Product Benefits

- Durability and long-life operation, thanks to the use of high-quality materials
- Stability in extreme weather conditions (physical controls)
- Easy transport
- Quick installation
- Installation availability for sloped or flat roof
- Flexibility and production precision, thanks to contemporary machinery



**NEO PLUS**  
mounting structures



**NEO PLUS UNIVERSAL**

**Technical data**

|                                    |  |
|------------------------------------|--|
| Approved collector models          | all sizes(1,5 to 2,9 m <sup>2</sup> ) with vertical or horizontal position |
| Approved nr of installed collector | 1 op 2   |
| Approved tank models               | 120 to 300 lt  |
| Inclination range [°]              | 15-75 or parallel to sloped roof   |
| Structure material                 | steel  |
| Structure surface treatment        | hot-dip galvanization or aluzinc or magnelis process                       |
| Structure thickness [mm]           | 1,5 or 2   |
| Collector support type             | C-shape or T-shape   |
| Connection material                | galvanized or inox 304 steel   |
| Connection to ground               | standard included solution or according to customer specification          |
| Labeling                           | according to customer specification to material, nr, position and language |
| Packaging                          | carton box or bulk or according to customer specification                  |
| Palletizing                        | according to customer specification  |



**92.000** Total m<sup>2</sup> of plant area  
**528.000** Average m<sup>2</sup> of absorbent surface produced annually  
**44 years** of experience

2nd km Argos-Nafplio | 21200, Argos, Greece  
 tel: +30 27510 20920-2

[www.dimas-solar.gr](http://www.dimas-solar.gr) | [sales@dimas-solar.gr](mailto:sales@dimas-solar.gr)